

**PRECAUTIONS:** Avoid direct contact. Skin and eye irritation may occur. Use in well-ventilated area. Inhalation of vapors may cause breathing difficulties. Recommended for interior use.  
**KEEP OUT OF REACH OF CHILDREN.**

For Chemical Emergency  
Spill, Leak, Fire, Exposure or Accident  
Call CHEMTREC Day or Night  
Within USA and Canada: **1-800-424-9300**  
Outside USA and Canada: 1-703-527-3887 (collect call accepted)

HMIS: Health - 3 Flammability - 1 Reactivity - 0

FOR PROFESSIONAL USE ONLY! THIN ONLY AS INSTRUCTED!  
VOC CONTENT: N/A DOT: Not DOT Regulated

Please refer to sds & technical data sheet prior to use of this product.  
Store at room temperature. Keep from freezing.  
Shelf Life: Up to one year in unopened container stored at room temperature.



#### Warning!

May be harmful if swallowed. May cause an allergic skin reaction. Causes eye irritation. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash hands and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.



Concrete Technology Incorporated

"Bringing Design and Beauty to Concrete"

# AQUA SHIELD 365 GLOSS COLORANT



TINT PACK FOR WATER BASED GLOSS URETHANE

This colorant is a high solids, concentrated, water based tint system specially formulated for Aqua Shield 365 WB Gloss Urethane. This colorant is formulated with high quality, ultra fine particle pigments that easily disperse in Aqua Shield 365 WB Gloss Urethane creating a superior solid colored finish.

**MIXING:** Mix one quart of colorant into two gallons of Resin (A) for 60 seconds using a squirrel mixer prior to mixing parts A&B together. Allow any foam to settle prior to use. Material may separate during long term storage. Remix as needed. Then mix the colored Part A with the appropriate amount of Catalyst (B) for another 60 seconds.

**PLEASE NOTE:** It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Usage and coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc.

**CAUTION:** Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmenting may cause color float or streaking, especially in the darker colors! Do not allow to puddle! The average usage is one quart (32 oz.) per 2.5 gallon kit of material depending upon desired opacity. For lighter colors it may take more, and darker colors may take less depending on the application.

Use this colorant with Aqua Shield 365 WB Gloss Urethane only.

**CLEAN-UP:** Use Soap and Warm Water. Dispose of containers in accordance with local and federal regulations.

Concrete Technology Inc.  
8770 133rd Ave N. | Largo, FL 33773 | Phone: 800-447-6573  
[www.designcti.com](http://www.designcti.com)

NET CONTENTS: 1 US QUART (3.3-3.5 LBS)