



105 Powdered Pigment

Product Data Sheet

DESCRIPTION

105 Powdered Pigment are conveniently premeasured to individually tint any single bag of 105 Grout. 105 Powdered Pigment are pure, synthetic, iron oxide pigments that contain no fillers that will affect the performance of the 105 Grout tinted. Color consistency is maintained from bag to bag.

MIXING AND APPLICATION

105 Grout Mix

1. Add required 111 or 112 Modifier to a 5 gallon as directed by the 105 Powdered Pigment TDS.
2. Empty 105 Powdered Pigment into modifier prior to addition of the 105 grout.
3. Mix with a handheld concrete mixing paddle.
4. While mixing, add 105 Powdered Pigment as directed in appropriate TDS. Note: multiple bag batches may be appropriate; always maintain mix ratio of 1, 105 Powdered Pigment to 1, 105 Grout.

SUITABILITY SAMPLE

Because job site conditions and requirements can vary significantly, always prepare a sample.

QUICK FACTS

Packaging: 0.5 – 1.5 lb. sack varies by color selection

Coverage: 1, 105 Powdered Pigment to 1, 50 lb. bag of 105 Grout

Color: 9 Standard Colors

Shelf Life: Under normal conditions when kept dry, out of direct sunlight, the shelf life of an unopened sack is 12 months from the date of purchase. Storage must be under roof and off the floor. Rotate inventory to maintain product that is within limits.

DISPOSAL

Contact your local government household waste coordinator for information on disposal of unused products.

LIMITATIONS

For use by trained professionals that have read the complete SDS. The aggregate of some 105 Powdered Pigment mixes may affect final color to vary from color chart. Always prepare a sample.

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price or replacement of product (if defective), at manufacturer's /seller's option. Concrete Technology Inc. shall not be liable for cost of labor or direct and/or incidental consequential damages.

CAUTIONS

KEEP OUT OF REACH OF CHILDREN. When used according to direction, no hazard is anticipated.

Inhalation: Avoid prolonged breathing of airborne dust, particularly present during mixing. Use NIOSH approved respirator for nuisance if threshold limit values are unsafe. Skin contact: Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. Eyes: Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

VOC REGULATORY COMPLIANCE

AIM

OTC

LADCO

CARB

SCAQMD

CANADA