

Technical Data Sheet

150/155 DYE PACK

COLOR PACK FOR SERIES 150/155 SOLVENT BASED SEALERS

150/155 Dye Pack is a high solids, concentrated, solvent based acrylic tint system specially formulated for series 150/155 solvent based acrylic sealers. 150/155 Dye Pack is formulated with high quality, ultra fine particle pigments that easily disperse in solvent based acrylic sealers. 150/155 Dye Pack is used to obtain a solid colored finish in many solvent based acrylic sealers.

Compliances - Specifications

Technical Information & Properties	
PROPERTY	VALUE
Solids/Active Content, Percentage by weight	Concentrated
Dry Time - Tack Free	See sealer data
Dry Time - Foot Traffic	See sealer data
Dry Time - Heavy Traffic	See sealer data
Re-Coat Time Window	See sealer data
Application Temperature	50° F - 80° F
VOC (Volatile Organic Compound) Content	N/A
Appearance - Wet	Depends on color
Appearance - Dry	Tinted and Med-High Gloss

Key Features

14 brilliant standard colors to choose from. (See color chart) *Includes black & white

Very economical, easy and decorative way to seal a variety of concrete substrates.

Easily disperses into most solvent based acrylic sealers.

Very easy way to create a beautiful, solid color concrete surface.

Recommended Applications

Driveways | Patios | Sidewalks | Many other concrete surfaces where a solid color sealing and dust proofing method is desired.



Information above is based on lab temperatures of 70° - 72°F at 50% RH. Using this product outside these conditions may affect the accuracy of the information above. Always test prior to use!

ALWAYS REFER TO SDS & READ FULL TECH DATA SHEET AND WARRANTY INFORMATION PRIOR TO USE.

150/155 DYE PACK

Precautions and Limitations

- This product will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- If using indoor, use proper ventilation while applying and for hours after application to ensure fumes are removed.
 - It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
 - This product performs best when applied as one or two medium-light coats, not one heavy coat.
- Please be aware that this product when cured may be slippery when wet. An anti-slip additive can be added to reduce slip hazards.
 - This product is not resistant to brake fluid, gasoline, and many similar products.
 - It is not recommended to thin product. Improper thinning may cause sealer to delaminate in a short time frame.
- This product may darken the surface of many new and existing concrete slabs. Test prior to use. Professional use only.
 - Follow the instructions for the solvent based acrylic sealer that is to be used for application guidelines.
- Solvent vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Application Instructions

SURFACE PREP: Concrete surface must be clean and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, the sealer may have white spots and have premature delamination and failure.

Review the technical data and MSDS for the chosen solvent based acrylic sealer prior to use for surface prep instructions, application instructions, coverage rates and limitations.

Substrate and air temperature must be no less than 40° F and not exceed 80° F. If applied outside these limits the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing. Note that in direct sunlight, substrate temperature can exceed 150° F which can cause extreme bubbling issues.

MIXING: Mix desired amount in a solvent based acrylic sealer for 1-2 minutes using a squirrel mixer prior to application. Allow any foam to settle prior to use. Material may separate during long term storage. Re-mix as needed.

USAGE RATE: Solid Opaque Finish: 8 ounces per gallon or 32 ounces (1 quart) per 5 gallon

*Usage rates are suggested amounts only! Due to varying sealer compositions, substrates, surface texture, porosity and desired look a test area is recommended to achieve desired results.

APPLICATION: Review the technical data and MSDS for the chosen solvent based acrylic sealer prior to use for surface prep instructions, application instructions, coverage rates and limitations.

FOR PERSONAL PROTECTION USE GLOVES, GOGGLES, AND RESPIRATORS.

CAUTION: Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmentation may cause color float or streaking, especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz.) per 5 gallons of material for most opaque applications. For lighter colors it may take more and darker colors may take less depending on the application as well as the composition of the solvent based acrylic sealer.

Check for compatibility with the solvent based acrylic sealer to be used prior to use!

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. When applying, do not exceed 400 sq. ft. per gallon. Applying too thin of a coating may cause inadequate film formation or performance expectations may be limited. **DO NOT USE ON BRICK.**

COF WARNING: OSHA and the American Disabilities Act (ADA) have now set enforceable standards for slip-resistance on pedestrian surfaces. The current coefficient of friction required by ADA is .6 on level surfaces and .8 on ramps. The manufacturer recommends the use of slip-resistant aggregate in all coatings or flooring systems that may be exposed to wet, oily or greasy conditions. It is the contractor and end users' responsibility to provide a flooring system that meets current safety standards. The manufacturer nor its sales agents will be responsible for injury incurred in a slip and fall accident.

CLEAN-UP: Use xylene. Dispose of containers in accordance with local, state and federal regulations.

PRODUCT REMOVAL: Refer to sealer technical data sheet.

SHELF LIFE: Up to one year from manufacture date in its original, unopened container stored at room temperature.

PACKAGING: Available in 1 quart containers.

Always read all technical information, label and SDS prior to use. This information can be found online or by calling customer service at the number below.